U.S. Pat. Appl. Ser. No. 10/600,853 Attorney Docket No. 10191/3107 Reply to Office Action of June 29, 2004

AMENDMENT TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

- 1. (Currently Amended) A system for triggering at least one restraining device comprising: at least one non-pedestrian-impact [[impact]] sensor for transmitting a first signal; at least one pedestrian-impact sensor for transmitting a second signal; and a processor for receiving the first and second signals, the processor being adapted to trigger the at least one restraining device as a function of a combination of the first and second signals.
- 2. (Original) The system according to claim 1, wherein the processor determines a crash type and a crash severity from the combination for the triggering of the restraining device.
- 3. (Original) The system according to claim 1, further comprising at least one of (a) at least one passenger sensor and (b) at least one precrash sensor, wherein the processor, in the triggering of the restraining device, further takes signals from the at least one of (a) and (b) into account.
- 4. (Original) The system according to claim 1, wherein the at least one pedestrian-impact sensor is situated in a front bumper of a vehicle.
- 5. (Original) The system according to claim 1, wherein the at least one pedestrian-impact sensor is situated in a rear bumper of a vehicle.
- 6. (Original) The system according to claim 1, wherein the at least one pedestrian-impact sensor is configured as a side-impact sensor.

2

U.S. Pat. Appl. Ser. No. 10/600,853 Attorney Docket No. 10191/3107

Reply to Office Action of June 29, 2004

7. (Currently Amended) The system according to claim 1, wherein the at least one <u>non-pedestrian-impact</u> [[impact]] sensor is embodied in a control device.

- 8. (Currently Amended) The system according to claim 1, wherein the at least one <u>non-pedestrian-impact</u> [[impact]] sensor includes a peripheral sensor.
- 9. (New) The system according to claim 1, wherein the at least one non-pedestrian-impact sensor includes at least one of an acceleration sensor and a deformation sensor.
- 10. (New) The system according to claim 9, wherein the deformation sensor includes one of a piezo sensor, an optical sensor, a temperature sensor, and a pressure sensor.
- 11. (New) The system according to claim 9, wherein the acceleration sensor is one of a micromechanical sensor and a switch.
- 12. (New) The system according to claim 1, wherein the pedestrian-impact sensor includes at least one of a piezo-foil, a strain gauge, an optical sensor, and a sensor of composite.
- 13. (New) The system according to claim 6, wherein the at least one pedestrian-impact sensor is situated in a trim molding of a vehicle.
- 14. (New) The system according to claim 1, wherein the at least one restraining device includes at least one of an airbag and a belt tightener.
- 15. (New) The system according to claim 1, wherein the processor triggers the at least one restraining device in a gradual manner.
- 16. (New) The system according to claim 1, wherein the processor triggers a particular one of a plurality of restraining devices based on a passenger weight.

NY01 719353 v 1 3

U.S. Pat. Appl. Ser. No. 10/600,853 Attorney Docket No. 10191/3107 Reply to Office Action of June 29, 2004

- 17. (New) The system according to claim 1, wherein the at least one pedestrian-impact sensor extends across an entire side of a vehicle.
- 18. (New) The system according to claim 3, wherein the at least one precrash sensor includes at least one of an ultrasound sensor, a video sensor, and a radar sensor.
- 19. (New) The system according to claim 1, wherein the restraining device is a vehicle-occupant restraining device.